



CLIENT TO ENSURE THAT THE SHADDED AREAS FREE FROM ANY OBSTRUCTIONS

TRACK HANGERS BY ASCOT TIED INTO ROOF STRUCTURE ABOVE (UP TO 1000mm MAX)

ISOLATOR & POWER SUPPLY BY CLIENT
 3 PHASE - WITH NEUTRAL & EARTH
 400 VOLT, 50 HZ, 16 AMP ISOLATOR WITH
 5 PIN CEE SOCKET TO BE POSITIONED
 1.7M FROM FLOOR WITHIN WIRE
 OF THE DOOR ON THE MOTOR SIDE
 CONTROL PANEL & 1.0M LONG ARMOURRED
 CABLE WITH 5 PIN CEE PLUG IS SUPPLIED
 BY ASCOT DOORS

OPERATION	
PANEL FINISH	
EXTERNAL COLOUR	
No. OF PANELS	
PANEL LENGTH	
DOOR WEIGHT	
CLIENT TO ENSURE:-	
1. OPENING IS PLUMB AND SQUARE.	
2. NO OBSTRUCTIONS OR SERVICES INTERFERE WITH OUR INSTALLATION.	
3. STRUCTURE IS CAPABLE OF CARRYING AN APPROX DOOR WEIGHT OF 15KG SQM WITHOUT DEFLECTION.	
4. TO MINIMISE INGRESS OF WATER IT IS RECOMMENDED THAT THE FLOOR SLAB SLOPES AWAY FROM THE DOOR.	

ascot
DOORS

BRITANNIA WAY
INDUSTRIAL
PARK
UNION ROAD
BOLTON
BL2 2HE
Tel: 01204 545801
Fax: 01204 545800

CONTRACTOR CLIENT -

PROJECT ADDRESS -

Drawn By

DATE -

Checked By

Approved By

REV DESCRIPTION

BY CHK

DATE

TITLE: LOW HEADROOM SECTIONAL OVERHEAD DOOR

EXTRAS: CABLE BREAK DEVICE

DRAWING No:

PROJECTION